Sports Flooring System DYNAMIK Flexi-Beam Elite Sprung Timber Sports Floor





The DYNAMIK Flexi-Beam Elite system is a cradle and beam sprung area elastic sports floor. It incorporates Flexi-Beams which support a 22mm premium engineered sports board. The system can be packed and levelled to take out variations in the sub floor.

The structure of the Flexi-Beam Elite system incorporates Flexi-Beams to provide a stable base for the 22mm board and allows for underfloor heating and insulation to be incorporated between the beams. Given it can be packed and levelled off a structural slab, the requirement for a levelling screed is avoided.

Flexi-Beam Elite Benefits

- Meets the requirements of EN 14904
- Sport England compliant
- Packed & levelled construction
- Underfloor heating compatible

- Complies with the latest ESFA specification
- Factory finished sports lacquer
- 25 year warranty
- Enhanced acoustic properties

Surface Finishes

The Flexi-Beam Elite engineered sports board is available in four different wood species:



European Oak

Official Partners







Canadian Maple





1	Premium Engineered Sports Board	22mm
2	Flexi-Beam	27mm
3	Sports Cradle: 100mm x 100mm x 10mm	10mm
4	Levelling Shims	To Suit Void
System Thickness (excluding levelling shims) A minimum void (drop in screed) of 75mm is required to install, pack and level the system.		59mm

Thickness of cradles/beams can vary dependent on void depth up to 100mm. For a greater void than 100mm, cradle-base packers can be used.

Performance Characteristics

Certification - EN14904	Class A4
Shock Absorption	55% < 75%
Vertical Deformation	2.3mm < 5.0mm
Rolling Load	≥1,500 N
Ball Rebound	≥ 90%
Slip Resistance	80 - 110

Specification Downloads

Visit Us



Product Specification downloads for our DYNAMIK products are available through NBS Source.



Product specifications may be subject to change without notice, please contact DYNAMIK for the latest product information

Sports Flooring

Acoustic Walling

Track & Gym