



The DYNAMIK Internal Decorative Panels provide a durable and cost-effective solution for any environment to reduce echo and reverberant noise levels. The Timber Slat Acoustic Panels are attractive and a great sound-absorbing solution that can be fitted on walls and ceilings. Ideal for use within Sports halls, schools, universities, leisure centres, reception areas and any are where sound absorption is required.

Principle Features

Acoustics – Our sound absorbing timber slats offer Class A acoustic performance (when installed on min. 40mm timber battens without insulation).

Time & Cost Savings – The panels are easily installed to any solid surface providing a cost effective acoustic solution.

Fire Performance – The panels are fire rated to European class B-s1-d0 on the polyster backing panel.

Colours - Panels are available in 5 attractive timber style finishes to provide a modern appearance that complements any design.

Colours




Light Oak



Smoked Oak



Grey Oak



Charcoa Grey



Walnut

Technical & Performance Specifications - Timber Slat Acoustic Panels

Panel Sizes	2,400mm x 605mm (Other panel size available for Light Oak only)
Panel Depth	22mm
Fire Performance	European class B - s1, d0
Acoustic Performance	Class A (with 40mm Airgap)
Applications	Schools, Universities, Reception Areas, Leisure Centres, Gyms

**Product specifications may be subject to change without notice, please contact DYNAMIK for the latest product information*